

BX51100

BX51100 adopts economic design, and is tailor-made for residential & light commercial. This LFP battery module supports remote update and APP monitoring and provides multiple installation options - wall-mounted, floor-standing and stack. It is scalable from 5.12 - 153 kWh (max. 30 modules in parallel), providing various energy storage options to meet different requirements.



APP Monitoring (optional)
Real-time monitoring
& Remote upgrade available



Module Design
Flexible expansion



Various Mounting Methods
Wall-mounted,
floor-standing and stacked



High Safety LFP
Cell level monitoring and balancing



Wide Compatibility
Matching with leading inverters

Technical Specifications

Model	BX51100
Battery Type	LiFePO4
Nominal Battery Energy	5.12 kWh
Nominal Capacity	100Ah
Nominal Voltage	51.2V
Operating Voltage	44.8 ~ 57.6V
Recomended Charge & Discharge C Rate	0.5C
Recommended Charge/Discharge Current	50A
Max Continous Charge/Discharge Current	75A
Peak Power Charge/Discharge Current	100A (15s)
Depth of Discharge (DOD)	90%
Net Weight	50kg
Dimension[W*D*H]	558*545*150mm
Charging Temp. Range	0~55°C
Discharging Temp. Range	-20~55°C
Communication	CAN/RS485/RS232
Cycle Life ^[1]	≥6000 Cycles
Protection Level	IP20
Expansion	Up to 30 units in parallel
Pros	Can be used in both off-grid and hybrid setups, compact design
Certification & Safety Standard	UN38.3/CE-EMC/GOST-R/IEC62619/IEC60730
Compatible inverters	Goodwe/Victron/Imeon/Solis/Luxpower/Growatt /GMDE/Sofar/Voltronic/Deye, etc.

[1]Test conditions: 0.5C Charging/Discharging, @25°C, 80% DOD

Distributed by BatteryMAX | www.batterymax.pk